

8303 Handheld Airborne Particle Counter

0.1 CFM (2.83 LPM)

- Industry's highest concentration of 15,000,000 particles/ft³ @ 10% coincidence loss
- Ideal for use in research, industrial health and safety, indoor air quality, and cleanroom applications
- Up to 10 hours continuous operation on a fully charged battery
- Industry's first Sleep Mode and Power Conservation Mode with Intelligent Battery
- The most comprehensive internal self-diagnostics of any handheld particle counter
- Real-Time Meter detects particle contamination sources with visual and audible indication
- Internet of Things (IoT) communication allows for network or cloud-based data options



The PMT® 8303 Handheld Particle Counter measures 0.3 to 25.0 μm with a flow rate of 0.1 CFM (2.83 LPM).

Easy to configure, this instrument displays up to 3 user-selectable size channels as well as temperature and relative humidity. View data and generate ISO 14644-1, EU GMP Annex 1 or FS 209E reports on screen or via printer, USB key, real time through its versatile output options or export to IMS (*Instrument Management Software*) data-download software. PMT® counters can be controlled and monitored remotely via web browser. The 8303 has a mass concentration mode that approximates density in $\mu\text{g}/\text{m}^3$.


All PMT® counters meet ISO 21501-4 and JIS B9921. The 8303 ensures compliance with an on-board pulse height analyzer.

Features and Benefits


- Measures 0.3 μm to 25.0 μm
- 0.1 CFM (2.83 LPM) flow rate
- Long life laser diode technology
- Measures up to 3 channels of simultaneous data
- Approximates mass concentration in $\mu\text{g}/\text{m}^3$ with density and refractive index corrections
- Integrated handle for one-handed operation
- Large easy-to-use icon driven color touch screen display
- Temperature and relative humidity probe included
- Stores up to 45,000 sample records, 1,000 sample locations and 50 recipes
- Annotation function allows user to save 32 character notations to a sample record
- Remote diagnostics allows for remote service investigation through the Internet
- Easy configuration and transferable from instrument to instrument
- Connect using Ethernet, USB or (optional) Wireless 802.11 b/g,
- Displays user-definable reports for ISO 14644-1, EU GMP Annex 1 and FS 209E
- Internal audible alarm with comprehensive alarm management
- User-selectable channel sizes
- Complies with ISO 21501-4 and JIS B9921 standards
- Seamless integration into a facility monitoring system
- Lightweight high-impact injection molded plastic enclosure
- 5 year warranty.

Specifications


Model	8303
Size Range	0.3 to 25 µm
Size Channels	Factory calibrated at 0.3, 0.5, 1.0 µm variable binning
Flow rates	0.1 CFM (2.83 LPM)
Concentration Limits	15,000,000 particles/ft ³ @ 10% coincidence (per ISO 21501-4), 30,000,000 particles/ft ³ @ 10% coincidence (as tested and validated)
Battery Run Time	>10 hours continuous operation
Light Source	Long life laser diode
Counting Efficiency	50% @ 0.3 µm; 100% for particles >0.45 µm per JIS
Zero Count	<1 count / 60 minutes (<1 particles / 6 ft ³). No fault count subtraction.
Count Modes	Real-Time Meter and graph, cumulative/differential count/m ³ and count/ft ³ , and mass concentration (PM)
Count Alarms	1 to 9,999,999 counts
Display	4.3" (10.9 cm) WQVGA (480×272) color touch screen
Printer	(Optional) External thermal printer available
Vacuum Source	Internal pump with automatic flow control
Filtered Exhaust	Internal HEPA filter
Number of Channels	3
Custom Size Channels	Calibration for custom size channels available
Audible Alarm	Adjustable built-in alarm
Battery	Removable Li-ion (Recharge time: 4 hours within instrument, <2 hours with external battery charger)
Reports	ISO 14644-1, EU GMP Annex 1, FS 209E
Recipes	50 user-configurable recipes
Communication Modes	Ethernet and USB. (Optional) Wireless 802.11 b/g
Environmental Sensor	Includes temperature 32° to 122°F (0° to 50°C) ±1°F (0.5°C) and relative humidity probe 15-90% ±2%
Alarm	Alarms on counts for all particle sizes, sensor failure, environmental sensors and flow
Standards	ISO 21501-4 and JIS B9921
External Surface	High impact injection molded plastic
Dimensions (L x W x H)	5.12" x 4.25" x 12.26" (13.0 cm x 10.8 cm x 31.1 cm) includes handle and does not include probes
Weight	2.2 lb (1.0 kg)
Accessories	Operating manual and IMS software on USB flash drive, isokinetic probe, temperature relative humidity sensor, filter, battery, USB cable, power supply and cable, Calibration certificate
Optional Accessories	Printed manual, carrying case, spare battery, external battery charger, external printer and isokinetic probes, barbed fittings
Buffer Memory	45,000 sample records (rotating buffer) including particle count data, environmental data, locations, annotations, and times. Scrollable on screen or printout
Sample Locations	Up to 1,000 locations 20 characters long
Sample Time	1 second to 99 hours
Power	110 to 240 VAC 50/60 Hz universal in-line power supply
Operating Conditions	41° to 104°F (5° to 40°C) / 20% to 95% non-condensing
Storage Conditions	32° to 122°F (0° to 50°C) / Up to 98% non-condensing
Warranty	5 year warranty Blower warranty : 1 year
Calibration frequency	Recommended minimum once per year
Calibration	NIST traceable



Audible and Visual Alarm Management



Real-Time Meter Pinpoints Particles Sources



Icon Driven Menus for Ease-of-Use

